TRUFLEX PAINT STICKS

Product: 9510

Section 1 : PRODUCT AND COMPANY IDENTIFICATION		
Manufacturer:	Truflex/Pang Rubber Products Company, Inc. 200 East Coshocton Street P.O. Box 486 Johnstown, Ohio 43031.	
Manufacturer emergency phone number:	Chemtrec 800–424–9300. International: 703–527–3887.	
Supplier:	Same as manufacturer.	
Product name:	Truflex paint sticks (MSDS #951)	
Product uses:	Marking crayons/paint sticks.	
Catalog number(s):	948(markal "B" white) and 948Y(markal "B" yellow), 950(yellow); best-brite tone/Pang 951, 951R, 951Y, 951B, and 951G.	
Effective date:	2010/9/20	
Revision No.:	0	
Last review:	2010/9/20	
Chemical family:	Mixture.	
NFPA:		

Section 2 : INGREDIENT INFORMATION					
C.A.S.	Concentration% wgt/wgt	Ingredient Name	ACGIH–TLV TWA	LD/50	LC/50
8001-26-1	<40	LINSEED OIL AND DERIVATIVES		NOT AVAILABLE	NOT AVAILABLE

Section 3 : HAZARD IDENTIFICATION

Route of entry: Skin contact, eye contact, inhalation and ingestion.

Effects of acute exposure

Eye contact:	May cause mild irritation.
	May cause redness and tearing.
	May cause stinging.
	May cause swelling.
Skin contact:	May cause skin burns.
	May cause mild irritation.
	May cause drying and cracking.
	May cause redness or burning sensation.
Inhalation:	May cause irritation.

Ingestion:	May cause nausea, vomiting and diarrhea.	
	May cause gastro-intestinal irritation.	
	No hazard known for ingestion of small quantities.	

Effects of chronic exposure: See effects of acute exposure.

	Section 4 : FIRST AID MEASURES
Skin contact:	Remove contaminated clothing. Wash with mild soap and water. Consult a physician if irritation persists.
Eye contact:	Flush with water for at least 15 minutes, holding eyelids open with fingers. Consult a physician if irritation persists.
Inhalation:	Remove victim to fresh air. If irritation persists, seek medical attention.
Ingestion:	Induce vomiting by giving two glasses of water. Never give anything by mouth to an unconscious person. If irritation occurs, consult a physician.
Additional information:	The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any inaccuracies.
	Section 5 : FIRE FIGHTING MEASURES
Flammability:	Not flammable.
Conditions of flammability:	At temperatures at or above flash point. Contaminated rags may catch fire spontaneously.
Extinguishing media:	Carbon dioxide, dry chemical, foam.
Special procedures:	Self-contained breathing apparatus required. Firefighters should wear the usual protective gear.
Auto-ignition temperature:	Not available.
Flash point (°C), method:	>204 (>400°F)
Lower flammability limit (% vol):	Not available.
Upper flammability limit (% vol):	Not available.
Explosion Data	
Sensitivity to static discharge:	Not available.
Sensitivity to mechanical impact:	Not available.
Hazardous combustion products:	Oxides of carbon (CO, CO2). Aldehydes. Various hydrocarbons.
Rate of burning:	Not available.
Explosive power:	Not available.

Section 6 : ACCIDENTAL RELEASE MEASURES

Leak/Spill: Prevent entry into drains, sewers, and other waterways. Wear appropriate protective equipment. Wash down with water after material pick up is complete. Allow molten material to cool. Scrape or shovel into containers.

Section 7 : HANDLING AND STORAGE

•	Wash thoroughly after using, particularly before eating or smoking. Wear personal protective equipment appropriate to task. Avoid breathing vapors. Avoid contact with skin, eyes and clothing. Keep rags immersed in water after usage. Launder contaminated clothing prior to reuse. Do not ingest.
Storage requirements:	Store at room temperature. Keep from freezing. Store in a cool and dry place. Store away from strong acids or oxidizers.

Section 8 : EXPOSURE CONTROLS / PERSONAL PROTECTION

Precautionary Measures

Gloves/Type:	Protective gloves for sensitive skin.
Respiratory/Type:	None normally required.
Footwear/Type:	As per local regulations.
Clothing/Type:	Normal work clothes.
Other/Type:	Eye wash facility should be in close proximity. Emergency shower should be in close proximity.
Ventilation requirements:	Normal ventilation.
Exposure limit of material:	Not available.

Section 9 : PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Solid

Appearance & odor:Various colors.
Cylindrical wax stick.
Slight paint odor.Odor threshold (ppm):Not available.Vapour pressure (mmHg):Not available.Vapour density (air=1):>1Volatiles (%)By volume:Not available.

Evaporation rate (butyl acetate = 1): Not volatile.

Boiling point (°C):	@ 760 mm Hg. >176.7 (>350°F)
Freezing point (°C):	(melting point). ~66 (150°F)
pH:	Not available.
Specific gravity @ 20 °C:	(water = 1). >1
Solubility in water (%):	Not available.
Coefficient of water\oil dist.:	Not available.
VOC:	(lb/gal). 0

Section 10 : STABILITY AND REACTIVITY

Chemical stability:	Product is stable.
Conditions of instability:	None known.
Hazardous polymerization:	Will not occur.
Incompatible substances:	Strong acids. Strong oxidizing agents.
Hazardous decomposition products:	See hazardous combustion products.

Section 11 : TOXICOLOGICAL INFORMATION

LD50 of product, species & route: Not available.

LC50 of product, species & route: Not available. Sensitization to product: Not available. Reproductive effects: Not available. Teratogenicity: Not available. Mutagenicity: Not available. Synergistic materials: Not available.

Section 12 : ECOLOGICAL INFORMATION

Environmental toxicity: No data at this time.

Environmental fate: No data at this time.

Section 13 : DISPOSAL CONSIDERATIONS

Waste disposal: In accordance with municipal, provincial and federal regulations.

Section 14 : TRANSPORT INFORMATION

ADR CLASSIFICATION: Not regulated.

Special shipping information: See transportation information.

Section 15 : REGULATORY INFORMATION

EU Regulatory Information

European Union (EU) Regulatory Information:	This product is not dangerous as defined by the European Union.
EU Risks:	Not applicable.
EU Safety:	Not applicable.
EINECS#:	CAS# 8001–26–1 – EINECS# 232–278–6.
EU Classification:	Not applicable.

Section 16 : OTHER INFORMATION

Supplier MSDS date: 2002/08/07

Data prepared by: Global Safety Management 3340 Peachtree Road, #1800 Atlanta, GA 30326

> Phone: 877–683–7460 Fax: (877) 683–7462

Web: www.globalsafetynet.com Email: info@globalsafetynet.com.

See www.techtirerepairs.com for the latest MSDSs.